

PRODUCT TECHNICAL SPECIFICATION

BRASS BALL VALVE, THREADED

SCOPE

Brass Ball Valve, Threaded, Brass
Sizes and Materials comply with EN Standards
in accordance with the TS EN 13547 Standard and certified
in accordance with the EN ISO 228-1 Thread Standard
DN 15, 20, 25, 32, 40, 50, 65*, 80*, 100*
PN 25

A. MATERIALS

Body	Brass
Bonnet	Brass
Ball	Brass
Sealing	PTFE (Teflon)
Components	
Stem	Brass
Lever	St-37 + Vinyl Coating

B. CONNECTION DIMENSIONS

in accordance with the EN ISO 228-1 Standards

C. NOMINAL PRESSURE / OPERATING PRESSURE

PN 25 / 25 Bar

D. OPERATING TEMPERATURE RANGE

-10 ~ +120 °C

E. MARKING

Minimal marking that is legible and obtained in the form of embossing from casting;

MANUFACTURER (BRAND)

BODY MATERIAL: **CW617N**

PRESSURE GRADING: **PN25**

NOMINAL SIZE: **DN15 / DN20 / DN25 / DN32 / DN40/DN50 / DN65 / DN80 / DN100**

F. TEST

in accordance with the EN 12266-1 Standard; RATE-A

G. WARRANTY

2-year warranty against workmanship and material defects

H. PACKAGING AND SHIPMENT

Shipped in cardboard boxes in plastic bags