

PRODUCT TECHNICAL SPECIFICATION

AIR DISCHARGE DEVICE (AIR VENT)

SCOPE

Automatic Air Vent

Materials comply with TSE 7817 Standards

1/2"

| | | |
|---|------------------------|--|
| 5 | Çek Vana / Check Valve | CuZn40Pb2 - CW617N - Pirinç Dövme / Forced Brass |
|---|------------------------|--|

A. MATERIALS

| | |
|--------------------------|--|
| Body | in accordance with the TS 7817 Standard; CuZn40Pb2 |
| Bonnet | in accordance with the TS 7817 Standard; CuZn40Pb2 |
| Safety Valve | in accordance with the TS 7817 Standard, Ebonite (Rigid Plastic) |
| Float | in accordance with the TS 7817 Standard, Ebonite (Rigid Plastic) |
| Plugs/Check valve | in accordance with the TS 7817 Standard, CuZn40Pb2 |

B. CONNECTION DIMENSIONS

Plug and air vent dimensions 1/2"

C. DIMENSIONS

Ø dimension 34mm in accordance with the TS 7817 Standard (Ømax.45mm),
Length 58 mm in accordance with the TS 7817 Standard (max. 80 mm)

D. NOMINAL PRESSURE / OPERATING PRESSURE

PN 10 / 10 Bar

E. OPERATING TEMPERATURE RANGE

-10 ~ +110 °C

F. MARKING

Minimal marking that is legible and obtained in the form of embossing from forging;

MANUFACTURER (BRAND)
OPERATING TEMPERATURE: **110 °C**
PRESSURE GRADING: **PN10**
STANDARD NUMBER: **TS 7817**

H. TEST

EN 12266-1 Inner and Outer Tightness

I. WARRANTY

2-year warranty against workmanship and material defects

J. PACKAGING AND SHIPMENT

Plastic plugs in fluid bore openings
Products are shipped as packed in individual plastics bags